

主动式温控箱

充电制式

通过空调系统保持温控箱内部温度

0 ~ 25°C

Envirotainer®
The Active Cold Chain



RAPe2
(1100kg)



RKNe1
(635kg)

5 ~ 20°C

Envirotainer®
The Active Cold Chain



Releye RAP
(1100kg)



Releye RLP
(880kg)

4 ~ 25°C

Safe
Global



RAP
(1213kg)



RKN
(646kg)

2 ~ 30°C

DeKaSch
TEMPERATURE SOLUTIONS



RAP
(1140kg)



RKN
(670kg)

干冰制式

通过循环风扇保持温控箱内部温度

-20 ~ 20°C

Envirotainer®
The Active Cold Chain



RAPt2
(450kg)



RKNT2
(265kg)

-5 or 5°C

ANA



RAP
(533kg)



RKN
(290kg)

被动式温控箱

被动制式

通过 Phase Change Material (PCM) 或 Vacuum Insulation Panels (VIPs) 保持温控箱内部温度

-25 ~ -15°C



TWINx	TLx	USx	EUROx
a: 800kg	a: 660kg	a: 575kg	a: 440kg
b: 800kg	b: 660kg	b: 575kg	b: 440kg
c: 905kg	c: 740kg	c: 640kg	c: 510kg

2 ~ 8°C

va-Q-tec



15 ~ 25°C

-80 ~ -20°C

SKY CELL



1500DF
(470kg)

2 ~ 8°C

SKY CELL



1500X
Model COL
(379kg)



1500C
(497kg)



2500C
(650kg)

15 ~ 25°C

SKY CELL



1500X
Model CRT
(379kg)



1500CRT
(497kg)



2500CRT
(650kg)

※各个温控箱的租赁受机场和租赁条件的限制，详情请咨询当地销售人员。
 ※干冰制式温控箱易受外界温度影响，特别是在夏季和冬季可能会偏离理想的温度范围。
 ※图中所示重量为各自温控箱自重