

## Active Container

### Electric type

Maintaining inner temperature with air-conditioning system

0 ~ 25°C

**Envirotainer®**  
The Active Cold Chain



RAPe2  
(1100kg)



RKNe1  
(635kg)

5 ~ 20°C

**Envirotainer®**  
The Active Cold Chain



Releye RAP  
(1100kg)



Releye RLP  
(880kg)

4 ~ 25°C

**Safe**  
Global



RAP  
(1213kg)



RKN  
(646kg)

2 ~ 30°C

**DeKaSch**  
TEMPERATURE SOLUTIONS



RAP  
(1140kg)



RKN  
(670kg)

### Dry-Ice type

Maintaining inner temperature with circulation fan

-20 ~ 20°C

**Envirotainer®**  
The Active Cold Chain



RAPt2  
(450kg)



RKNt2  
(265kg)

-5 or 5°C

**ANA**



RAP  
(533kg)




RKN  
(290kg)

## Passive Container

### Passive type

Maintaining inner temperature with Phase Change Material (PCM) and/or Vacuum Insulation Panels (VIPs)

-25 ~ -15°C



TWINx	TLx	USx	EUROx
a: 800kg	a: 660kg	a: 575kg	a: 440kg
b: 800kg	b: 660kg	b: 575kg	b: 440kg
c: 905kg	c: 740kg	c: 640kg	c: 510kg

2 ~ 8°C

**va-Q-tec**

15 ~ 25°C



-80 ~ -20°C

**SKY CELL**



1500DF  
(470kg)

2 ~ 8°C

**SKY CELL**



1500X  
Model COL  
(379kg)



1500C  
(497kg)



2500C  
(650kg)

15 ~ 25°C

**SKY CELL**



1500X  
Model CRT  
(379kg)



1500CRT  
(497kg)



2500CRT  
(650kg)

※The available airports and lease conditions of each container differs. For details, please kindly contact our Sales in charge.

※Due to the Dry-Ice type being easily impacted by the ambient temperature, especially during the summer or winter seasons, the required temperature may possibly be deviated.

※Tare weight by each temperature container is specified in the chart.